



MOTOR W/SLIDE BASE 1800 RPM, 230/460 V, 3 PH, 60 HZ		
HP	FRAME	TYPE
40	324T	ODP
50	326T	TEFC
60	364T	TEXP
75	365T	SEVERE DUTY TEFC
		SEVERE DUTY TEXP

BLOWER	A	B
5514-84/85	6 FLG	20 ⁵ / ₈
5516-84/85	8 FLG	21 ⁵ / ₈
5518-84/85	8 FLG	22 ⁵ / ₈

APPROXIMATE WEIGHT

BASE, DRIVE & GUARD-	628	LBS
BLOWER	-	LBS
MOTOR & SLIDE BASE	-	LBS
TOTAL WEIGHT	-	LBS

THIS OUTLINE APPLIES TO THE BLOWERS & MOTORS SHOWN IN TABLES

NOTE:

1 EXTERNAL LUBE SYSTEM MUST BE LOCATED SO THAT SLOPE FROM BLOWER DRAIN TO TANK INLET IS NOT LESS THAN 1'-0" IN 6'-0" AND NO PART OF DRAIN HOSE TO BE BELOW THE TANK INLET.

Tuthill 800.825.6937

BASE MOUNTED OUTLINE B5500VV3L-L

SIZE:
C2

DR BD 9-27-95

CH LB 9-27-95